

							CE symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland							Name and address of manufacturer
CEDOP07 MEDITE EXTERIOR MDF.H-2							DOP reference
EN 13986:2004+A1:2015							Reference to harmonised standard
Not Applicable							Notified body number
04							Year in which the CE mark was first affixed
E1 (E05)							Formaldehyde classification
MDF.H-2							Product technical class
External use as non-structural components							Intended use
<b>Thickness Range mm</b>	3 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30	Thickness range
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.70	0.70	0.80	0.80	0.75	0.75	Declared performance
<b>Swelling in thickness %</b>	30	18	12	10	8	7	
<b>Internal bond after boil test (N/mm<sup>2</sup>)</b>	0.20	0.20	0.15	0.15	0.12	0.12	
<b>Reaction to fire</b>	NPD	NPD	NPD	D-s2,d0	D-s2,d0	D-s2,d0	
<b>Release of formaldehyde <sup>1</sup></b>	E1	E1	E1	E1	E1	E1	
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	
<b>Biological</b>	Use classes 1,2, 3						

<sup>1</sup>: Release of formaldehyde ≤ 0.062 mg/m<sup>3</sup> (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.