

DECLARATION OF PERFORMANCE MEDITE EXTERIOR

Reference Number: **CEDOP07**

MEDITE EUROPE DAC
Redmondstown, Clonmel
County Tipperary
Ireland

Product Type	Intended Use	AVCP*	Notified Body Reference
MDF.H-2	External use as non-structural components	4	Not Applicable

*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011

Declared Performance

Essential characteristics	Performance						Harmonised technical specification
	3 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30	
Thickness Range							EN 13986:2004+A1:2015
Bending strength (N/mm ²)	27	27	27	26	24	22	
Internal bond (N/mm ²)	0.70	0.70	0.80	0.80	0.75	0.75	
Moisture Resistance Internal bond after boil test (N/mm ²)	0.20	0.20	0.15	0.15	0.12	0.12	
Thickness Swelling (24hrs) %	30	18	12	10	8	7	
Release of formaldehyde ¹	E1	E1	E1	E1	E1	E1	
Reaction to fire ²	NPD	NPD	NPD	D-s2,d0	D-s2,d0	D-s2,d0	
Water vapour permeability μ	NPD	NPD	NPD	NPD	NPD	NPD	
Airborne sound insulation (R)	NPD	NPD	NPD	NPD	NPD	NPD	
Thermal conductivity (W/m.K)	0.14	0.13	0.13	0.13	0.13	0.13	
Biological durability	Use Classes 1,2 & 3 (coated)						
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	

¹: Release of formaldehyde ≤ 0.062 mg/m³ (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.

²: Mounted without air gap directly on a substrate class A1 or A2-s1, d0 with minimum density 10kg/m³ or on a substrate at least class D-s2,d0 with minimum density 400kg/m³. Or mounted with a closed or open-air gap not more than 22mm, on a substrate at least class A2-s1, d0 with minimum density 10kg/m³.

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Guillaume Coste, Technical Services Manager.

Clonmel, Ireland. 13/04/2026.