

UK CA							UKCA symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland							Name and address of manufacturer
CADOP07 MEDITE EXTERIOR MDF.H-2							DOP reference
EN 13986:2004+A1:2015							Reference to Designated Standard
Not Applicable							Approved Body number
2021							Year in which the UKCA mark was first affixed
E1 (E05)							Formaldehyde classification
MDF.H-2							Product technical class
External use as non-structural components							Intended use
Thickness Range mm	3 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30	Thickness range
Internal bond (N/mm²)	0.70	0.70	0.80	0.80	0.75	0.75	Declared performance
Swelling in thickness %	30	18	12	10	8	7	
Internal bond after boil test (N/mm²)	0.20	0.20	0.15	0.15	0.12	0.12	
Reaction to fire	NPD	NPD	NPD	D-s2,d0	D-s2,d0	D-s2,d0	
Release of formaldehyde ¹	E1	E1	E1	E1	E1	E1	
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	
Biological	Use classes 1,2, 3						

¹: Release of formaldehyde ≤ 0.062 mg/m³ (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.