

**DECLARATION OF PERFORMANCE**  
**MEDITE EXTERIOR**  
Reference Number: **CADOP07**  
**MEDITE EUROPE DAC**  
**Redmondstown, Clonmel**  
**County Tipperary**  
**Ireland**

Product Type	Intended Use	AVCP*	Approved Body Reference
MDF.H-2	External use as non-structural components	4	Not Applicable
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

**Declared Performance**

Essential characteristics	Performance						Designated Standard
	3 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30	
Thickness Range							EN 13986:2004+A1:2015
Bending strength (N/mm <sup>2</sup> )	27	27	27	26	24	22	
Internal bond (N/mm <sup>2</sup> )	0.70	0.70	0.80	0.80	0.75	0.75	
Moisture Resistance Internal bond after boil test (N/mm <sup>2</sup> )	0.20	0.20	0.15	0.15	0.12	0.12	
Thickness Swelling (24hrs) %	30	18	12	10	8	7	
Release of formaldehyde <sup>1</sup>	E1	E1	E1	E1	E1	E1	
Reaction to fire <sup>2</sup>	NPD	NPD	NPD	D-s2,d0	D-s2,d0	D-s2,d0	
Water vapour permeability	NPD	NPD	NPD	NPD	NPD	NPD	
Airborne sound insulation (R)	NPD	NPD	NPD	NPD	NPD	NPD	
Thermal conductivity	NPD	NPD	NPD	NPD	NPD	NPD	
Biological durability	Use Classes 1,2 & 3 (coated)						
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	

<sup>1</sup>: Release of formaldehyde ≤ 0.062 mg/m<sup>3</sup> (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.

<sup>2</sup>: Mounted without air gap directly on a substrate class A1 or A2-s1, d0 with minimum density 10kg/m<sup>3</sup> or on a substrate at least class D-s2,d0 with minimum density 400kg/m<sup>3</sup>. Or mounted with a closed or open-air gap not more than 22mm, on a substrate at least class A2-s1, d0 with minimum density 10kg/m<sup>3</sup>.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:



Guillaume Coste, Technical Services Manager.

Clonmel, Ireland. 13/04/2026.