

## DECLARATION OF PERFORMANCE

**MEDITE LITE**

**MEDITE TRADE**

Reference Number: **CEDOP44**

**MEDITE EUROPE DAC**

**Redmondstown,**

**Clonmel, County Tipperary**

**Ireland**

Product Type	Intended Use	AVCP*	Notified Body Reference
L-MDF	Internal use as non-structural components in dry conditions	4	Not Applicable
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

### Declared Performance

Essential characteristics	Performance				Harmonised technical specification
	>6 to 9	>9 to 12	>12 to 19	>19 to 25	
Thickness Range	>6 to 9	>9 to 12	>12 to 19	>19 to 25	EN 13986:2004+A1:2015
Bending strength (N/mm <sup>2</sup> )	20	20	18	15	
Internal bond (N/mm <sup>2</sup> )	0.45	0.45	0.45	0.45	
Thickness Swelling (24hrs) %	20	16	14	12	
Release of formaldehyde <sup>1</sup>	E1	E1	E1	E1	
Reaction to fire	NPD	NPD	NPD	NPD	
Water vapour permeability	NPD	NPD	NPD	NPD	
Airborne sound insulation (dB)	NPD	NPD	NPD	NPD	
Sound absorption 250Hz to 500Hz (α)	0.10	0.10	0.10	0.10	
Sound absorption 1000Hz to 2000Hz (α)	0.20	0.20	0.20	0.20	
Thermal conductivity (W/m.K)	0.11	0.11	0.11	0.11	
Biological durability	Use Class 1				
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	

<sup>1</sup>: Release of formaldehyde ≤ 0.062 mg/m<sup>3</sup> (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Guillaume Coste, Technical Services Manager.

Clonmel, Ireland. 13/04/2026