

			CE symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland			Name and address of manufacturer
CEDOP59 MEDITE MR LITE L-MDF.H			DOP reference
EN 13986:2004+A1:2015			Reference to harmonised standard
Not Applicable			Notified body number
04			Year in which the CE mark was first affixed
E1 (E05)			Formaldehyde classification
L-MDF.H-1			Product technical class
Internal use as non-structural components in humid conditions			Intended use
<b>Thickness Range mm</b>	>9.0 to 12.0mm	>12.0 to 19.0mm	Thickness range
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.45	0.45	
<b>Swelling in thickness %</b>	16	13	Declared performance
<b>Internal bond after cyclic test (N/mm<sup>2</sup>)</b>	0.25	0.20	
<b>Swelling in thickness after cyclic test %</b>	16	15	
<b>Reaction to fire</b>	D-s2,d0	D-s2,d0	
<b>Release of formaldehyde <sup>1</sup></b>	E1	E1	
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	
<b>Biological</b>	Use Class 1 & 2	Use Class 1 & 2	

<sup>1</sup>: Release of formaldehyde ≤ 0.062 mg/m<sup>3</sup> (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.