

**DECLARATION OF PERFORMANCE
MEDITE MR LITE**Reference Number: **CADOP19****MEDITE EUROPE DAC****Redmondstown****Clonmel****County Tipperary****Ireland**


Product Type	Intended Use	AVCP*	Approved Body Reference
L-MDF.H-1	Internal use as non-structural components in humid conditions	4	Not Applicable
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

Declared Performance

Essential characteristics	Performance		Designated Standard
Thickness Range	>9.0 to 12.0mm	>12.0 to 19.0mm	EN 13986:2004+A1:2015
Internal bond (N/mm ²)	0.45	0.45	
Swelling in thickness (%)	16	13	
Internal bond after cyclic test (N/mm ²)	0.25	0.20	
Swelling in thickness after cyclic test (%)	16	15	
Release of formaldehyde	E1	E1	
Reaction to fire	D-s2,d0	D-s2,d0	
Water vapour permeability μ	NPD	NPD	
Airborne sound insulation (surface mass) (R)	NPD	NPD	
Sound absorption Frequency range 250Hz to 500Hz (α)	NPD	NPD	
Sound absorption Frequency range 1000Hz to 2000Hz (α)	NPD	NPD	
Thermal conductivity λ	NPD	NPD	
Biological durability	Use Classes 1 & 2	Use Classes 1 & 2	
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:



Tom Prendergast, Technical Manager.

Clonmel, Ireland. 12/07/2021