

			UKCA symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland			Name and address of manufacturer
CADOP59 MEDITE MR LITE L-MDF.H			DOP reference
EN 13986:2004+A1:2015			Reference to Designated Standard
Not Applicable			Approved Body number
2021			Year in which the UKCA mark was first affixed
E1 (E05)			Formaldehyde classification
L-MDF.H-1			Product technical class
Internal use as non-structural components in humid conditions			Intended use
Thickness Range mm	>9.0 to 12.0mm	>12.0 to 19.0mm	Thickness range
Internal bond (N/mm ²)			Declared performance
	0.45	0.45	
Swelling in thickness %	16	13	
Internal bond after cyclic test (N/mm²)	0.25	0.20	
Swelling in thickness after cyclic test %	16	15	
Reaction to fire	D-s2,d0	D-s2,d0	
Release of formaldehyde ¹	E1	E1	
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	
Biological	Use Class 1 & 2	Use Class 1 & 2	

¹: Release of formaldehyde ≤ 0.062 mg/m³ (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.