

				CE symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland				Name and address of manufacturer
CEDOP53 MEDITE MR WIDE				DOP reference
EN 13986:2004+A1:2015				Reference to harmonised standard
Not Applicable				Notified body number
24				Year in which the CE mark was first affixed
E1 (E05)				Formaldehyde classification
MDF.H-1				Product technical class
Internal use as non-structural components in humid conditions				Intended use
Thickness Range mm	>9 to 12	>12 to 19	>19 to 25	Thickness range
Internal bond (N/mm²)	0.80	0.75	0.75	Declared performance
Swelling in thickness %	10	8	7	
Internal bond after cyclic test (N/mm²)	0.25	0.20	0.15	
Swelling in thickness after cyclic test %	16	15	15	
Reaction to fire	D-s2,d0	D-s2,d0	D-s2,d0	
Release of formaldehyde ¹	E1	E1	E1	
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	
Biological	Use Class 1 & 2			

¹: Release of formaldehyde ≤ 0.062 mg/m³ (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.