

				UKCA symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland				Name and address of manufacturer
CADOP13 MEDITE MR WIDE				DOP reference
EN 13986:2004+A1:2015				Reference to Designated Standard
Not Applicable				Approved Body number
2024				Year in which the UKCA mark was first affixed
E1				Formaldehyde classification
MDF.H-1				Product technical class
Internal use as non-structural components in humid conditions				Intended use
<b>Thickness Range mm</b>	>9 to 12	>12 to 19	>19 to 30	Thickness range
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.80	0.75	0.75	Declared performance
<b>Swelling in thickness %</b>	10	8	7	
<b>Internal bond after cyclic test (N/mm<sup>2</sup>)</b>	0.25	0.20	0.15	
<b>Swelling in thickness after cyclic test %</b>	16	15	15	
<b>Reaction to fire</b>	D-s2,d0	D-s2,d0	D-s2,d0	
<b>Release of formaldehyde</b>	E1	E1	E1	
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	≤5ppm	
<b>Biological</b>	Use Class 1 & 2			