

DECLARATION OF PERFORMANCE MEDITE PREMIER FR EUROCLASS B

Reference Number: **CADOP50**

MEDITE EUROPE DAC
Redmondstown, Clonmel
County Tipperary, Ireland

Product Type	Intended Use	AVCP*	UK Assessment Body
L-MDF	Internal use as non-structural components in dry conditions	1	EFFECTIS UK Ltd 2822
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

Declared Performance

Essential characteristics	Performance			Harmonised technical specification
Thickness Range (mm)	12	>12 to 19	>19 to 25	BS EN 13986:2004+A1:2015
Bending strength (N/mm ²)	20	18	15	
Internal bond (N/mm ²)	0.45	0.45	0.45	
Swelling in thickness (24hrs) %	16	14	12	
Release of formaldehyde ¹	E1	E1	E1	
Reaction to fire	B-s1,d0	B-s1,d0	B-s1,d0	
Reaction to fire: Field of application	Valid with or without horizontal and vertical butt joints. Valid with an air gap up to 40mm. Valid on any substrate with thickness ≥ 9mm, of fire performance A2-s2, d0 or better, and density ≥ 652.5kg/m ³ (Excl. paper faced gypsum plasterboard)			
Airborne sound insulation (R)	NPD	NPD	NPD	
Sound absorption 250Hz to 500Hz (α)	0.10	0.10	0.10	
Sound absorption 1000Hz to 2000Hz (α)	0.20	0.20	0.20	
Thermal conductivity (W/m.K)	0.11	0.11	0.11	
Biological Durability	Use Class 1			
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	

¹: Release of formaldehyde ≤ 0.062 mg/m³ (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Guillaume Coste, Technical Services Manager.

Clonmel, Ireland. 13/04/2026.