

**DECLARATION OF PERFORMANCE  
MEDITE PREMIER FR EUROCLASS B**Reference Number: **CEDOP50****MEDITE EUROPE DAC  
Redmondstown, Clonmel  
County Tipperary, Ireland**

Product Type	Intended Use	AVCP*	Notified Body Reference
L-MDF	Internal use as non-structural components in dry conditions	1	EFFECTIS France 1812
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

**Declared Performance**

Essential characteristics	Performance			Harmonised technical specification
	12	>12 to 19	>19 to 25	
Thickness Range (mm)	12	>12 to 19	>19 to 25	<b>EN 13986:2004+A1:2015</b>
Bending strength (N/mm <sup>2</sup> )	20	18	15	
Internal bond (N/mm <sup>2</sup> )	0.45	0.45	0.45	
Swelling in thickness (24hrs) %	16	14	12	
Release of formaldehyde <sup>1</sup>	E1	E1	E1	
Reaction to fire	B-s1,d0	B-s1,d0	B-s1,d0	
Reaction to fire: Field of application	Valid with or without horizontal and vertical butt joints. Valid with an air gap up to 40mm. Valid on any substrate with thickness ≥ 9mm, of fire performance A2-s2, d0 or better, and density ≥ 652.5kg/m <sup>3</sup> . (excl. paper faced gypsum plasterboard)			
Airborne sound insulation (R)	NPD	NPD	NPD	
Sound absorption 250Hz to 500Hz (α)	0.10	0.10	0.10	
Sound absorption 1000Hz to 2000Hz (α)	0.20	0.20	0.20	
Thermal conductivity (W/m.K)	0.11	0.11	0.11	
Biological Durability	Use Class 1			
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	

<sup>1</sup>: Release of formaldehyde ≤ 0.062 mg/m<sup>3</sup> (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Guillaume Coste, Technical Services Manager.

Clonmel, Ireland. 13/04/2026.