

DECLARATION OF PERFORMANCE MEDITE PREMIER FR EUROCLASS B

Reference Number: **CADOP11**

MEDITE EUROPE DAC
Redmondstown, Clonmel
County Tipperary, Ireland

Product Type	Intended Use	AVCP*	UK Assessment Body
MDF	Internal use as non-structural components in dry conditions	1	Warringtonfire 1121
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

Declared Performance

Essential characteristics	Performance		Harmonised technical specification
	4 to 6	>6 to 9	
Thickness Range (mm)	4 to 6	>6 to 9	BS EN 13986:2004:A1:2015
Internal bond (N/mm ²)	0.65	0.65	
Swelling in thickness (24hr) %	30	17	
Release of formaldehyde	E1	E1	
Reaction to fire	B-s2,d0	B-s2,d0	
Water vapour permeability μ	NPD	NPD	
Airborne sound insulation (surface mass) (R)	NPD	NPD	
Sound absorption Frequency range 250Hz to 500Hz (α)	NPD	NPD	
Sound absorption Frequency range 1000Hz to 2000Hz (α)	NPD	NPD	
Thermal conductivity	NPD	NPD	
Biological Durability	Use Class 1		
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Guillaume Coste, Technical Services Manager.

Clonmel, Ireland. 17/05/2023