

<b>UK CA</b>				UKCA symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland				Name and address of manufacturer
CADOP50 MEDITE PREMIER FR L-MDF EUROCLASS B				DOP reference
BS EN 13986:2004+A1:2015				Reference to harmonised standard
EFFECTIS UK Ltd 2822				UK Assessment body and Number
22				Year in which the CE mark was first affixed
E1 (E05)				Formaldehyde classification
L-MDF				Product technical class
Internal use as non-structural components in dry conditions				Intended use
<b>Thickness Range mm</b>	12	>12 to 19	>19 to 25	Thickness range
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.45	0.45	0.45	Declared performance
<b>Swelling in thickness %</b>	16	14	12	
<b>Reaction to fire</b>	B-s1,d0	B-s1,d0	B-s1,d0	
<b>Release of formaldehyde <sup>1</sup></b>	E1	E1	E1	
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	≤5ppm	
<b>Biological</b>	Use Class 1			

<sup>1</sup>: Release of formaldehyde ≤ 0.062 mg/m<sup>3</sup> (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.