

| | | | |
|---|-------------|---------|--|
| UK CA | | | UKCA symbol |
| MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland | | | Name and address of manufacturer |
| CADOP51 MEDITE PREMIER FR MDF EUROCLASS B | | | DOP reference |
| BS EN 13986:2004+A1:2015 | | | Reference to harmonised standard |
| EFFECTIS UK Ltd 2822 | | | UK Assessment body and Number |
| 22 | | | Year in which the CE mark was first affixed |
| E1 (E05) | | | Formaldehyde classification |
| MDF | | | Product technical class |
| Internal use as non-structural components in dry conditions | | | Intended use |
| Thickness Range mm | 4 to 6 | >6 to 9 | Thickness range |
| Internal bond (N/mm²) | 0.65 | 0.65 | Declared performance |
| Swelling in thickness % | 30 | 17 | |
| Reaction to fire | B-s2,d0 | B-s2,d0 | |
| Release of formaldehyde ¹ | E1 | E1 | |
| Release (content) of pentachlorophenol (PCP) | ≤5ppm | ≤5ppm | |
| Biological Durability | Use Class 1 | | |

¹: Release of formaldehyde ≤ 0.062 mg/m³ (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.