

						CE symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland						Name and address of manufacturer
CEDOP42 MEDITE PREMIER MDF						DOP reference.
EN 13986:2004+A1:2015						Reference to harmonised standard
Not Applicable						Notified body number
04						Year in which the CE mark was first affixed
E1 (E05)						Formaldehyde classification
MDF						Product technical class
Internal use as non-structural components in dry conditions						Intended use
<b>Thickness Range mm</b>	3 to 4	>4 to 6	>6 to <9	>25 to 30	>30 to 45	Thickness range
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.65	0.65	0.65	0.55	0.50	Declared performance
<b>Swelling in thickness %</b>	35	30	17	10	8	
<b>Reaction to fire</b>	NPD	NPD	NPD	D-s2,d0	D-s2,d0	
<b>Release of formaldehyde <sup>1</sup></b>	E1	E1	E1	E1	E1	
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	
<b>Biological</b>	Use Class 1					

<sup>1</sup>: Release of formaldehyde ≤ 0.062 mg/m<sup>3</sup> (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.