

UK CA						UKCA symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland						Name and address of manufacturer
CADOP42 MEDITE PREMIER MDF						DOP reference
EN 13986:2004+A1:2015						Reference to Designated Standard
Not Applicable						Approved Body number
2021						Year in which the UKCA mark was first affixed
E1 (E05)						Formaldehyde classification
MDF						Product technical class
Internal use as non-structural components in dry conditions						Intended use
Thickness Range mm	3 to 4	>4 to 6	>6 to <9	>25 to 30	>30 to 45	Thickness range
Internal bond (N/mm²)	0.65	0.65	0.65	0.55	0.50	Declared performance
Swelling in thickness %	35	30	17	10	8	
Reaction to fire	NPD	NPD	NPD	D-s2,d0	D-s2,d0	
Release of formaldehyde ¹	E1	E1	E1	E1	E1	
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	
Biological	Use Class 1					

¹: Release of formaldehyde ≤ 0.062 mg/m³ (≤ 0.05ppm) in accordance with requirements of Regulation (EU) 2023/1464 – E05.