

					
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland					
CEDOP09 MEDITE TRICOYA EXTREME MDF.H-2					
EN 13986:2004+A1:2015					
Not Applicable					
04					
E1					
MDF.H					
External and internal use as non-structural components					
Thickness Range mm	4 to <9	9 to <12	12 to <15	15 to <18	18
Internal bond (N/mm ²)	0.80	0.80	0.80	0.80	0.80
Swelling in thickness %	2.5	2.0	2.0	1.5	1.5
Internal bond after boil test (N/mm ²)	0.65	0.65	0.65	0.65	0.65
Reaction to fire	NPD	E-s2,d0	E-s2,d0	E-s2,d0	E-s2,d0
Release of formaldehyde	E1	E1	E1	E1	E1
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm
Thermal resistance R Value m ² k / W	0.056	0.085	0.114	0.150	0.180
Biological	Use Classes 1,2,3, 4				

CE symbol

Name and address of
manufacturer
DOP reference

Reference to harmonised
standard

Notified body number

Year in which the CE mark
was first affixed

Formaldehyde classification

Product technical class

Intended use

Thickness range

Declared performance